

SC 45TW

Scanjet tank cleaning equipment



Scanjet Model SC 45TW can be used for fixed installation on down pipe or for portable cleaning on a flexible hose.

SC 45TW is available in bronze or stainless steel versions and is therefore suitable for any type of tank cleaning operation. Our range of accessories, such as hoses, hose saddles, hose connectors or adapters, y-pieces and valves also covers any type of operation.

Typical applications for SC 45TW:

- Crude oil carriers
- Product carriers
- Offshore
- Bulk carriers
- OBO carriers
- FPSO & FSU

Accessories:

Connections



To suit any type of connection, various types of adapters and connectors are available in suitable materials for the marine environment.



The standard hose comes with two stainless steel bonded wires for electrostatic protection.

KEY FEATURES

SC 45TW

- Optimised cleaning effect
- Easy handling
- Safe operation
- Designed for long lifetime
- Media lubricated

SC 45TW



Portable tank cleaning set including SC 45TW, flexible hose and hose saddle.




Distributed and Serviced by...
Tank Cleaning Technologies, Inc.
15200 Middlebrook Drive, Suite E
Houston, Texas 77058 - USA
Phone: +1 281 480 4041
Fax: +1 713 516 5083
Email: sales@tankcleantech.com

www.tankcleantech.com


Stocking Locations in USA, Canada and Mexico



Technical performance




Water flow for selection of different nozzles sizes at specific inlet pressure.




Effective jet length for selection of different nozzles sizes at specific inlet pressure.

(Performance data according to DNV type approval certificate)



SC 45 TW mounted on Twinfix downpipe.

Dimensions



Specifications

Flow	14 - 60 m³/h
Inlet pressure	0,6 - 1,2 MPa
Recommended pressure	0,8 MPa
Max temperature	95°C
Rotation speed	1 - 3 rpm
Approx weight	14 kg
Standard connection	2" BSP male
Material in contact with cargo	AISI 316 or bronze
Bearing and sealings	PTFE/PEEK
Lubrication	Cleaning media